


NOTE: END CAP TO BE IMPRESSION STAMPED WITH "Applicable PART NUMBER."

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
GF540	6.0	.100	.10	1.26	10,000	C-8
GF550	6.0	.200	.40	5.03	5,000	C-8
GF570	6.3	.250	.64	8.04	10,000	C-8
GF560	6.3	.300	.64	8.04	10,000	C-8
GF660	8.0	.150	.40	5.03	10,000	C-8
GF665	8.0	.200	.25	3.14	10,000	C-8
GF650	8.0	.200	.56	7.00	10,000	C-8
GF670	8.0	.250	.64	8.04	10,000	C-8
GF680	8.0	.300	.90	11.31	10,000	C-8
GF710	12.0	.100	.23	2.89	10,000	C-8
GF780	12.0	.150	.70	9.00	5,000	C-8
GF740	12.6	.300	.64	8.04	5,000	C-8

METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
				TITLE T-2 FUSE STYLE (3AG) LAMPS					
DRAWN BY L. WENGSTROM		APPVD BY DATE L.R. 3/23/17		SIZE A	FSCM NO. 55335	DRAWING NO. FUSE GF SERIES T-2			
REV. NO. A ADD PART NO. GF650 RELEASED 3/23/17		APPVD DATE 3/1/01		SCALE NONE		RELEASED DATE 3/1/01	REVISION DATE 3/23/17	REV. NO. A	SHEET 1 OF 1
DESCRIPTION/ECO NUMBER		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED							