

AE-B56-NM1

DIP40/BGA56 specialized adapter for FLASH memory.
Device package dimensions: 7.7 x 9.0 x 1.0 mm, 0.75 mm pitch.



Click the programmer model below to get an appropriate list of the devices supported by the adapter:

- [ChipProg+](#)
- [ChipProg-40](#)
- [ChipProg-48, ChipProg-G4](#)

Adapter Connection Table:

DIP-40	BGA-56	U1, 74HC573	U2, 74HC573	C1, 150pF	C2, 0.1uF
1	E1,G6				
2					
3		11	11	1	
4	B5				
5					
6					
7	C5				
8					
9	A5				
10	C7				
11	A7				
12	B7				
13	A8				
14	B8				
15	C8				
16	D8				
17	E8				
18					
19					

20	A3,F1,G2,G8,C4,B4	1, 10	1, 10	2	2
21	E7				
22	F8				
23	F7	2			
24	G7		2		
25	E6	3			
26	F6		3		
27	E5	4			
28	F5		4		
29	G5	5			
30	F4		5		
31	E4	6			
32	D5		6		
33	G3	7			
34	F3		7		
35	E3	8			
36	F2		8		
37	G1	9			
38	E2		9		
39					
40	A4,G4,D6	20	20		1
			12		
	D7		13		
	D1	12			
	D2	13			
	C1	14			
	B1	15			
	A1	16			
	C2	17			
	B2	18			
	A2	19			
	C6		16		
	B3		15		
	C3		14		
	A6		17		
	B6		18		
	D4		19		