



PIN No.	CONFIGURATION	FUNCTION
1	STBY+	+5V,0.5A FOR STBY
2	STBY-	RETURN OF STBY
3	NC	NO CONNECTION
4	NC	NO CONNECTION
5	R-	REMOTE ON/OFF -
6	R+	REMOTE ON/OFF +
7	NC	NO CONNECTION
8	NC	NO CONNECTION
9	NC	NO CONNECTION
10	TOVP	FOR INTERNAL TEST
11	S-	REMOTE SENSE-
12	S+	REMOTE SENSE+

NOTES

- A : M4 TAPPED HOLES (4) FOR CUSTOMER CHASSIS MOUNTING.
 SCREW PENETRATION DEPTH 4mm MAX, RECOMMENDED TORQUE : 1.27N·m(13kgf·cm)
- B : M3 SCREWS(7) FOR I/P & O/P TB, RECOMMENDED TORQUE: 0.49N·m(5.0kgf·cm)

CONNECTORS USED:

PART DESCRIPTION	PART NAME	MANUFACT.	QTY
CN52	S12B-PHDSS(LF)(SN)	J.S.T	1
TB1	B825-01-03P-K	TIANLI	1
TB51	B825-01-04P-K	TIANLI	1

(unit : mm)

MODEL NAME	CUS350M
TDK-Lambda	

CA820-02-01A