

## Specification Sheet

Part Number: T50L5C2



Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Green, 100/pkg

|                     |  |
|---------------------|--|
| Article Number      | 111-05445  |
| Type                | T50L   |
| Color               | Green (GN)   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul> |
| Quantity Per        | bag  |

### Product Description

HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Green, 100/pkg

**Global Part Name**

T50L-PA66-GN

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225.0

**Length L (Imperial)**

15.35

**Length L (Metric)**

390.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.19

**Width W (Metric)**

4.8

**Bundle Diameter Min (Imperial)**

0.06

**Bundle Diameter Min (Metric)**

1.5

**Bundle Diameter Max (Imperial)**

4.3

**Bundle Diameter Max (Metric)**

109.2

|                             |     |
|-----------------------------|-----|
| <b>Thickness T (Metric)</b> | 1.4 |
|-----------------------------|-----|

|                 |                      |
|-----------------|----------------------|
| <b>Material</b> | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

|                          |      |
|--------------------------|------|
| <b>Material Shortcut</b> | PA66 |
|--------------------------|------|

|                    |            |
|--------------------|------------|
| <b>US MIL SPEC</b> | MS3367-2-5 |
|--------------------|------------|

|                    |  |
|--------------------|--|
| <b>SAE-AS33671</b> |  |
|--------------------|--|

**Flammability**

|          |                     |
|----------|---------------------|
| UL 94 V2 | <b>Halogen free</b> |
|----------|---------------------|

|     |                                       |
|-----|---------------------------------------|
| Yes | <b>Operating Temperature (Metric)</b> |
|-----|---------------------------------------|

|                                  |                       |
|----------------------------------|-----------------------|
| -40°F to +185°F (-40°C to +85°C) | <b>ROHS Complaint</b> |
|----------------------------------|-----------------------|

|     |  |
|-----|--|
| Yes | <b>Certification/Specification WEB</b> |
|-----|--|

|                                |                           |
|--------------------------------|---------------------------|
| UL-ZODZ.E64139 CAGE Code 53421 | <b>UL Recognized (US)</b> |
|--------------------------------|---------------------------|

|     |                                  |
|-----|----------------------------------|
| Yes | <b>UL Listed (US and Canada)</b> |
|-----|----------------------------------|

|     |                                      |
|-----|--------------------------------------|
| Yes | <b>UL Recognized (US and Canada)</b> |
|-----|--------------------------------------|

|     |  |
|-----|--|
| Yes |  |
|-----|--|

|                                   |     |
|-----------------------------------|-----|
| <b>Package Quantity(Imperial)</b> | 100 |
|-----------------------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>Package Quantity (Metric)</b> | 100 |
|----------------------------------|-----|

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)