

## Network cable - VS-M12MS-PPC/ME-93E-LI/2,0 - 1406483

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Assembled Ethernet cable, CAT5e, shielded, 2-pair, AWG 26 stranded (7-wire), RAL 5021 (water blue), M12 plug on RJ45 plug/IP67 push-pull metal housing, line, length 2 m



### Key commercial data

Packing unit	1 PCE
GTIN	 4 046356 476126
Custom tariff number	85444210
Country of origin	POLAND

### Technical data

#### Mechanical characteristics

Number of positions	4
Number of slots	1
Shielded	Yes
Insertion/withdrawal cycles	≥ 100
Cable diameter	6.70 mm
Cable exit	Straight
Cable structure	2x2xAWG26/7; SF/UTP
Smallest bending radius, fixed installation	33.5 mm (cable, fixed installation)
Smallest bending radius, movable installation	33.5 mm (cable, flexible installation)
Length of cable	2 m
Ambient temperature (operation)	-25 °C ... 60 °C (cable, fixed installation)
	-5 °C ... 60 °C (cable, flexible installation)

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C (cable, fixed installation)
---------------------------------	--

## Network cable - VS-M12MS-PPC/ME-93E-LI/2,0 - 1406483

### Technical data

#### Ambient conditions

	-5 °C ... 60 °C (cable, flexible installation)
--	--

#### Material data

Inflammability class according to UL 94	V2
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021

#### Electrical characteristics

Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)
---	--

#### Line characteristics

Cable type	Ethernet
Cable structure	2x2xAWG26/7; SF/UTP
Conductor cross section	0.14 mm <sup>2</sup>
AWG signal line	26
Conductor structure signal line	7x 0.16 mm
Core diameter including insulation	1 mm
External cable diameter	5.90 mm
Wire colors	white/orange-orange, white/green-green
External sheath, color	water blue RAL 5021
Insulation resistance	≥ 5 GΩ*km
Conductor resistance	≤ 284 Ω/km
Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)
Working capacitance	48 nF (At 800 Hz)
Wave impedance	100 Ω ±15% (At 1 to 100 MHz)
Nominal voltage, cable	125 V
Test voltage Core/Core	1000 V
Test voltage Core/Shield	500 V
Twisted pairs	2 cores to the pair
Overall twist	Two pairs with two fillers to the core
Shielding	Plastic-coated aluminum foil, tinned copper braided shield
Optical shield covering	85 %
Outer sheath, material	PUR
Conductor material	Bare Cu litz wires
Smallest bending radius, fixed installation	30 mm (cable, fixed installation)
Smallest bending radius, movable installation	78 mm (cable, flexible installation)

# Network cable - VS-M12MS-PPC/ME-93E-LI/2,0 - 1406483

## Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27060307
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27061801

## ETIM


ETIM 3.0	EC000830
ETIM 4.0	EC002599
ETIM 5.0	EC000830

## UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501


## Drawings

Dimensioned drawing



Push-pull RJ45 connector IP65/67

Dimensioned drawing



Plug, M12 x 1, straight, shielded