


# SMD Power Inductor CDRH10D43R



## Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 10.8 × 10.5 × 4.5mm Max.
- Product weight: 1.6g (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.

## Environmental Data

- Operating temperature range: -40°C ~ +105°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +105°C
- Solder reflow temperature: 260 °C peak.


## Packaging

- Carrier tape and reel packaging
- 13" diameter reel
- 500pcs per reel



## Applications

- Ideally used in Game machine, Notebook PC, LCD TV, DVD, STB, Projector etc as DC-DC converter inductors.


## Dimension - [mm]



## Land pattern and Schematics - [mm]



1.2μH~22μH



33μH~100μH



### Electrical Characteristics

Part Name	Stamp	Inductance ( $\mu\text{H}$ ) [ within ] ※1	D.C.R. (m $\Omega$ ) Max. (Typ.) (at 20°C)	Saturation Current (A) ※2		Temperature Rise Current (A) ※3
				at 20°C	at 105°C	
CDRH10D43RNP-1R2PC	1R2	1.2 $\pm$ 25%	10.4(8.28)	12.0	9.0	7.2
CDRH10D43RNP-1R8PC	1R8	1.8 $\pm$ 25%	12.2(9.76)	11.2	8.5	6.6
CDRH10D43RNP-2R7PC	2R7	2.7 $\pm$ 25%	14.1(11.3)	9.5	7.3	6.0
CDRH10D43RNP-3R9PC	3R9	3.9 $\pm$ 25%	16.6(13.2)	8.8	6.9	5.8
CDRH10D43RNP-4R7PC	4R7	4.7 $\pm$ 25%	20.4(16.3)	8.0	6.5	4.8
CDRH10D43RNP-6R8PC	6R8	6.8 $\pm$ 25%	25.1(20.0)	7.0	5.6	4.6
CDRH10D43RNP-8R2PC	8R2	8.2 $\pm$ 25%	31.0(24.8)	6.0	4.8	4.2
CDRH10D43RNP-100MC	100	10 $\pm$ 20%	32.7(26.1)	5.2	4.3	4.1
CDRH10D43RNP-120MC	120	12 $\pm$ 20%	47.2(37.7)	4.9	4.0	3.2
CDRH10D43RNP-150MC	150	15 $\pm$ 20%	56.1(44.9)	4.5	3.7	3.1
CDRH10D43RNP-220MC	220	22 $\pm$ 20%	73.9(59.1)	4.0	3.2	2.7
CDRH10D43RNP-330MC	330	33 $\pm$ 20%	120.0(95.7)	3.1	2.6	2.0
CDRH10D43RNP-470MC	470	47 $\pm$ 20%	160.4(128.3)	2.6	2.1	1.7
CDRH10D43RNP-560MC	560	56 $\pm$ 20%	175.8(140.6)	2.4	2.0	1.6
CDRH10D43RNP-680MC	680	68 $\pm$ 20%	217.3(173.8)	2.2	1.8	1.4
CDRH10D43RNP-820MC	820	82 $\pm$ 20%	273.8(219.0)	2.0	1.6	1.2
CDRH10D43RNP-101MC	101	100 $\pm$ 20%	344.5(275.6)	1.8	1.4	1.1

※1 Inductance measuring condition: at 100kHz.

※2 The saturation current: This indicates the value of DC current when the inductance decreases to 65% of its nominal.













※3 The temperature rise: The value of DC current when the temperature rise is  $\Delta T=40^\circ\text{C}$  ( $T_a=20^\circ\text{C}$ ).

# SMD Power Inductor CDRH10D43R




## Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) —  $\Delta T$








# SMD Power Inductor CDRH10D43R




## Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) —  $\Delta T$




## Solder Reflow Condition

**Heat Endurance**



**Temperature Chart**



Please refer to the sales offices on our website - <http://www.sumida.com>

### Hong Kong

Tel.+852-2880-6781  
FAX.+852-2565-9600  
[sales@hk.sumida.com](mailto:sales@hk.sumida.com)

### Saitama(Japan)

Tel.+81-48-691-7300  
FAX.+81-48-691-7340  
[sales@jp.sumida.com](mailto:sales@jp.sumida.com)

### Chicago

Tel.+1-847-545-6700  
FAX. +1-847-545-6720  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

### Shanghai

Tel.+86-21-5836-3299  
FAX.+86-21-5836-3266  
[shanghai.sales@cn.sumida.com](mailto:shanghai.sales@cn.sumida.com)

### Seoul

Tel.+82-2-6237-0777  
FAX.+82-2-6237-0778  
[sales@kr.sumida.com](mailto:sales@kr.sumida.com)

### Obernzell

Tel.+49-8591-937-0  
FAX. +49-8591-937-103  
[contact@eu.sumida.com](mailto:contact@eu.sumida.com)

### Shenzhen

Tel.+86-755-8291-0228  
FAX.+86-755-8291-0338  
[shenzhen.sales@cn.sumida.com](mailto:shenzhen.sales@cn.sumida.com)

### Singapore

Tel.+65-6296-3388  
FAX.+65-6841-4426  
[sales@sg.sumida.com](mailto:sales@sg.sumida.com)

### Neumarkt

Tel.+49-9181-4509-110  
FAX. +49-9181-4509-310  
[infocomp@eu.sumida.com](mailto:infocomp@eu.sumida.com)

### Taipei

Tel.+886-2-8751-2737  
FAX.+886-2-8751-2738  
[sales@tw.sumida.com](mailto:sales@tw.sumida.com)

### San Jose

Tel.+1-408-321-9660  
FAX.+1-408-321-9308  
[sales@us.sumida.com](mailto:sales@us.sumida.com)